

LEGENDARY PERFORMANCE

Mythic

NON-TOXIC
PAINT

PRIME



- INTERIOR DRYWALL**
- DRYWALL & WOOD
 - LOW ODOR
 - SPATTER RESISTANT



- INT/EXT ACCENT PRIMER**
- ACCENT COLORS
 - MULTI SURFACE
 - LOW ODOR
 - MILDEW RESISTANCE



- INT/EXT PREMIUM HIDE**
- PREMIUM HIDE
 - MULTI SURFACE
 - LOW ODOR
 - MILDEW RESISTANCE



- INT/EXT ALL PURPOSE**
- DIRECT TO METAL
 - ALL PURPOSE
 - LOW ODOR
 - MILDEW RESISTANCE

Zero VOC
Volatile Organic Compounds
Excluding addition of colorant (untinted)



SAFE FOR
PEOPLE



SAFE FOR
PETS



SAFE FOR
the EARTH

This primer meets criteria for coatings used in LEED® and CHPS certified buildings.

4200 Mamie Street, Suite 120 · Hattiesburg, MS 39402 · Customer Support: 1.888.714.9422 · Fax: 1.888.714.9423

www.mythicpaint.com



PRIME

Mythic® Non-Toxic, Carcinogen-free primers provide a protective undercoat and promotes even topcoat development for a long lasting beautiful finish.

EQUIPMENT/PERTRECHOS

Conv. Spray:	40 PSI TIP:704/FX	Pistola convencional:	40 PSI TIP:704/FX
Airless Spray:	1800 - 2400 PSI TIP:.015"-.021"	Pistola sin aire:	1800 - 2400 PSI TIP:.015"-.021"
Brush:	Polyester or Nylon	Pincel:	Poliéster or Nylon
Roller:	3/8"- 1/2" Nap Cover	Rodillo:	3/8"- 1/2" Nap Cubierta
Pad:	Standard	Pad:	Estándar

THINNER & CLEAN UP/DILUYENTE Y LIMPIEZA

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.
No se recomienda diluir, pero si es necesario utilizar, limpiar el agua con moderación. El jabón y el agua de limpieza.

LIMITATIONS / LIMITACIONES

- Do not apply when air, surface, or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90°F (32°C).
- *No aplicar cuando la temperatura del aire, la superficie, o el producto está por debajo de 50 °F (10 °C) o si la temperatura puede descender a este nivel dentro de las 4 horas de la aplicación.*
- *No aplicar en temperaturas superiores a 90 °F (32 °C).*

PACKAGING / EMBALAJE

Quarts, Gallons, 5 Gallons, depending on product type.
Cuartos de galón, galones, 5 galones, dependiendo del tipo de producto.

COLORS / COLORES

Product can be tinted with up to 2 oz. of colorant per gallon.
El producto puede ser teñido con hasta 2 oz. de colorante por galón.

SPECIFICATION DATA / ESPECIFICACIONES TECNICAS

Product	Interior Drywall Primer MP710	Int/Ext Premium Hide Primer MP720	Int/Ext All Purpose Primer MP730	Int/Ext Accent Primer MP740	Producto
Type	Acrylic Latex				Tipo
Finish	2-7 @85°	10-15 @85°	15-20 @85°	2-7 @85°	Acabado
Volume Solids	23±2%	30±2%	31±2%	28±2%	volumen sólido
Wt./Gallon	10.61 lbs.	10.07 lbs.	10.24 lbs.	10.10 lbs.	Peso/ galón
VOC (max)	0 gm/ltr; 0 lbs/gal				VOC (máximo)
Dry Time	Touch: 1 hour; Recoat: 4 hours @ 77F, 50% RH				Tiempo de secado
Coverage	350-400 sq ft/gal @ 4 mils wet, 1 mil dry				Cobertura

4200 Mamie Street, Suite 120 · Hattiesburg, MS 39402 · Customer Support: 1.888.714.9422 · Fax: 1.888.714.9423

www.mythicpaint.com